

5-25x56 PM II - 5-25x56 PM II LP TREMOR3 1cm ccw DT27 MTC LT / ST ZC CT RAL 8000

[Optics & Mounting](#) > [Scopes](#) > [Rifle Scopes](#)

The 5-25×56 PM II from Schmidt and Bender stands at the pinnacle of variable-magnification tactical optics, engineered for long-range precision, outstanding clarity and professional-level reliability. With a wide 5-25× zoom range and a substantial 56 mm objective lens, it delivers exceptional light-gathering capability, enabling crisp, bright imagery even at extended distances.

Built upon a rugged 34 mm main tube, the scope accommodates large internal adjustment ranges and is designed for demanding use. It features a reticle in the first focal plane (FFP) so that scale and hold-offs remain accurate at any magnification. The field of view spans approximately 5.3-1.5 m at 100 m, while the exit pupil ranges around 11.0-2.3 mm, and the eye relief remains generous at around 90 mm. The parallax adjustment typically extends from 10 m to infinity, enabling accurate focus from very close ranges through to extreme distances.

The turret system is engineered for precision: click values as fine as 0.1 mrad (≈ 1 cm at 100 m) are available, and a double-turn elevation turret combined with single-turn windage allows vast usable correction ranges for wind and elevation. Optical transmission exceeds 90 %, and the construction is nitrogen-filled, fog- and waterproof, ensuring full reliability in all climatic conditions.

Key Specifications:

Magnification: 5-25×
Objective Lens Diameter: 56 mm
Main Tube Diameter: 34 mm
Field of View: approx. 5.3-1.5 m @100 m
Exit Pupil: approx. 11.0-2.3 mm
Eye Relief: approx. 90 mm
Parallax Adjustment: from ~10 m to infinity
Click Value: approx. 0.1 mrad (≈ 1 cm at 100 m)
Optical Transmission: > 90 %

Crafted in Germany to the highest standards, the 5-25×56 PM II is the go-to choice for military, law-enforcement and competition shooters who demand absolute clarity, mechanical integrity and extreme flexibility in one optic.

Attributes

- Name: [5-25x56 PM II LP TREMOR3 1cm ccw DT27 MTC LT / ST ZC CT RAL 8000](#)
- Manufacturer: [SCHMIDT U. BENDER](#)
- Product no.: EU2015857
- Mfr. No.: 689-945-552-G8-E8
- Colour: FDE
- Delivery weight: 2kg
- Shipping height: 100mm
- Shipping width: 100mm

NO IMAGE
AVAILABLE

- Shipping length: 450mm
- EAN: 4060537065657

Table of Contents

- [Startpage](#)
- [Safety Instruction Guide for the 5-25x56 PM II](#)
- [About Us](#)

Safety Instruction Guide for the 5-25x56 PM II

Introduction

Thank you for choosing the 5-25x56 PM II scope from Schmidt and Bender. This guide provides essential safety instructions and guidelines to ensure the safe use of your product. Please read this document carefully and keep it for future reference.

General Safety Guidelines

- **Product Safety:** This product has been designed with safety in mind. It meets the EU General Product Safety Regulation (GPSR) requirements.
- **Enhanced Recalls:** In the event of a safety issue, standardized recall notices will be provided, and remedies will be offered free of charge.
- **Online Shopping:** When purchasing online, you are entitled to the same safety protections as when buying from physical stores.
- **Special Consumer Focus:** Extra precautions are in place to protect vulnerable groups, including children.
- **EU Contact Point:** For any safety inquiries, please ensure you have access to an EU-based contact.
- **Rapid Alerts:** Stay informed about product safety through the Safety Gate system for timely updates on unsafe products.

Specific Safety Precautions for Use

- **Age Restrictions:** This product is intended for use by individuals aged 18 and older. Ensure that it is kept out of reach of children.
- **Avoid Direct Eye Exposure:** Do not look directly into the scope while pointing it at a bright light source, as this may cause eye damage.
- **Proper Handling:** Always handle the scope with care. Avoid dropping or subjecting it to strong impacts.
- **Moisture Protection:** Although the scope is nitrogen-filled and waterproof, avoid exposing it to excessive moisture for prolonged periods.
- **Cleaning:** Use only a soft, dry cloth to clean the lenses. Avoid using any abrasive materials or solvents that could damage the optics.
- **Storage:** Store the scope in a cool, dry place when not in use. Use the provided protective cover to shield it from dust and scratches.

Instructions for Installation and Usage

- **Mounting the Scope:**
 1. Ensure that your rifle is unloaded and pointed in a safe direction.
 2. Select a suitable mounting base that is compatible with the 34 mm main tube.
 3. Securely attach the scope to the mounting base, ensuring it is level and aligned with the rifle's bore.
 4. Tighten the mounting screws according to the manufacturer's specifications to avoid loosening during use.
- **Adjusting the Scope:**
 1. **Parallax Adjustment:** Adjust the parallax setting to match your shooting distance (from approximately 10 m to infinity).
 2. **Elevation and Windage:** Use the turret system to make adjustments. Each click corresponds to approximately 0.1 mrad (≈ 1 cm at 100 m).
 3. **Reticle Focus:** Adjust the eyepiece focus to ensure a clear reticle image.

- **Using the Scope:**

1. Position your eye at the recommended eye relief distance (approximately 90 mm) from the eyepiece.
2. Adjust the magnification according to your shooting needs (5–25×).
3. Ensure a proper shooting stance and aim at your target before taking a shot.

Disposal Instructions

- **Environmental Considerations:** Dispose of the scope responsibly in accordance with local regulations regarding electronic waste.
- **Recycling:** If possible, recycle components of the scope to minimize environmental impact. Check with local recycling programs for proper disposal methods.

Contact Information for Further Support

For any questions or concerns regarding the safety and use of your 5–25x56 PM II scope, please refer to the EU-based contact provided with your product purchase.

By following these safety guidelines and instructions, you can ensure a safe and enjoyable experience with your Schmidt and Bender 5–25x56 PM II scope. Thank you for your attention to these important safety measures.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk