

3-27x56 PM II High Power - 3-27x56 PM II High Power LP GR²ID 1cm cw DT II+ MTC LT / ST II ZC LT

[Optics & Mounting](#) > [Scopes](#) > [Rifle Scopes](#)

The 3-27x56 PM II High Power from Schmidt and Bender is a premier tactical riflescope engineered for ultimate versatility—capable of precise performance from near-range engagements all the way to extreme long-distance targets. With an expansive 3-27x magnification range, this scope adapts effortlessly across calibres and mission profiles.

Its 56 mm objective lens offers exceptional light gathering and clarity, enabling detailed target acquisition even at great distances. The field of view spans approximately 13.0-1.4 m at 100 m, while the exit pupil ranges around 8.7-2.1 mm. Generous eye relief of around 90 mm ensures comfortable alignment and a stable sight picture.

Built on a rugged 34 mm main tube, the scope is constructed for demanding environments. The turret system accommodates ultra-fine click values (e.g., ~0.1 mrad) and massive internal adjustment ranges for elevation and windage—making it suitable for long-range engagement scenarios. Parallax adjustment commonly spans from around 10 m to infinity, giving flexibility across varied target distances.

Key Specifications:

Magnification: 3-27x

Objective Lens Diameter: 56 mm

Main Tube Diameter: 34 mm

Field of View: approx. 13.0-1.4 m @100 m

Exit Pupil: approx. 8.7-2.1 mm

Eye Relief: approx. 90 mm

Click Value: approx. 0.1 mrad (~0.5 cm @100 m) depending on configuration

Parallax: from ~10 m to infinity

Crafted with German precision, the 3-27x56 PM II High Power is ideal for professionals, competition marksmen or hunters who demand the highest optical clarity, mechanical resilience and full versatility across a wide range of engagement distances.

Attributes

- Name: [3-27x56 PM II High Power LP GR²ID 1cm cw DT II+ MTC LT / ST II ZC LT](#)
- Manufacturer: [SCHMIDT U. BENDER](#)
- Product no.: EU2015942
- Mfr. No.: 669-911-422-M3-I6
- Colour: Black
- Delivery weight: 2kg
- Shipping height: 100mm
- Shipping width: 100mm
- Shipping length: 450mm
- EAN: 4060537062151

NO IMAGE
AVAILABLE

Table of Contents

- [Startpage](#)
- [Safety Instruction Guide for the 3-27x56 PM II High Power Riflescope](#)
- [About Us](#)

Safety Instruction Guide for the 3-27x56 PM II High Power Riflescope

Introduction

Thank you for choosing the 3-27x56 PM II High Power Riflescope by Schmidt and Bender. This guide provides essential safety instructions and guidelines to ensure the safe use and handling of your product. Please read this document carefully before using the riflescope.

General Safety Guidelines

- Ensure that the riflescope is used only for its intended purpose, which is for aiming and shooting with firearms.
- Always handle the riflescope with care to prevent damage to the optical components.
- Keep the riflescope out of reach of children and unauthorized users.
- Regularly inspect the riflescope for any signs of wear, damage, or malfunction. If any issues are found, discontinue use immediately and seek professional assistance.
- Follow all local laws and regulations regarding the use of firearms and optical sights.
- Be aware of your surroundings when using the riflescope, and ensure a safe shooting environment.

Specific Safety Precautions for Use

- Always use the riflescope in a safe and controlled environment. Avoid using it in crowded or uncontrolled areas.
- When adjusting the magnification or making any other adjustments, do so with the riflescope pointed in a safe direction.
- Ensure that the riflescope is securely mounted to the firearm before use. Follow the manufacturer's instructions for proper mounting.
- Use appropriate eye protection when using firearms equipped with the riflescope.
- Do not attempt to disassemble or modify the riflescope. Any alterations may void the warranty and compromise safety.
- Avoid exposing the riflescope to extreme temperatures, moisture, or direct sunlight for extended periods.

Instructions for Installation and Usage

1. Installation:

- Select a suitable mounting location on your firearm that allows for a clear line of sight.
- Securely attach the riflescope to the firearm using the provided mounting rings and base. Ensure that all screws are tightened to the manufacturer's specifications.
- Check the alignment of the riflescope to ensure it is level with the firearm.

2. Usage:

- Before use, familiarize yourself with the controls and features of the riflescope, including the magnification adjustment, parallax adjustment, and turret system.
- Adjust the magnification to the desired level based on your shooting distance and target size.
- Use the parallax adjustment to ensure a clear image at your target distance.
- When ready to shoot, ensure that the firearm is pointed in a safe direction, and follow all firearm safety protocols.
- After use, cover the riflescope with a protective cap or case to prevent dust and damage.

Disposal Instructions

- Dispose of the riflescope in accordance with local regulations regarding electronic waste and optical products.
- Do not dispose of the riflescope in regular household waste.
- Consider recycling options if available in your area.

Contact Information for Further Support

For safety inquiries or product support, please contact the manufacturer or authorized dealer. Ensure that you have the product model and any relevant information available when seeking assistance.

By following these safety instructions, you can ensure a safe and enjoyable experience with your 3-27x56 PM II High Power Riflescope. Thank you for your attention to safety and for choosing Schmidt and Bender.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk