

3-27x56 PM II High Power - 3-27x56 PM II High Power LP MSR2 0,05 mrad cw MT II MTC LT / DT II+ ZC LT

[Optics & Mounting](#) > [Scopes](#) > [Rifle Scopes](#)

The 3-27x56 PM II High Power from Schmidt and Bender is a premier tactical riflescope engineered for ultimate versatility—capable of precise performance from near-range engagements all the way to extreme long-distance targets. With an expansive 3-27x magnification range, this scope adapts effortlessly across calibres and mission profiles.

Its 56 mm objective lens offers exceptional light gathering and clarity, enabling detailed target acquisition even at great distances. The field of view spans approximately 13.0-1.4 m at 100 m, while the exit pupil ranges around 8.7-2.1 mm. Generous eye relief of around 90 mm ensures comfortable alignment and a stable sight picture.

Built on a rugged 34 mm main tube, the scope is constructed for demanding environments. The turret system accommodates ultra-fine click values (e.g., ~0.1 mrad) and massive internal adjustment ranges for elevation and windage—making it suitable for long-range engagement scenarios. Parallax adjustment commonly spans from around 10 m to infinity, giving flexibility across varied target distances.

Key Specifications:

Magnification: 3-27x

Objective Lens Diameter: 56 mm

Main Tube Diameter: 34 mm

Field of View: approx. 13.0-1.4 m @100 m

Exit Pupil: approx. 8.7-2.1 mm

Eye Relief: approx. 90 mm

Click Value: approx. 0.1 mrad (~0.5 cm @100 m) depending on configuration

Parallax: from ~10 m to infinity

Crafted with German precision, the 3-27x56 PM II High Power is ideal for professionals, competition marksmen or hunters who demand the highest optical clarity, mechanical resilience and full versatility across a wide range of engagement distances.

Attributes

- Name: [3-27x56 PM II High Power LP MSR2 0,05 mrad cw MT II MTC LT / DT II+ ZC LT](#)
- Manufacturer: [SCHMIDT U. BENDER](#)
- Product no.: EU2015945
- Mfr. No.: 669-911-842-I6-H6
- Colour: Black
- Delivery weight: 2kg
- Shipping height: 100mm
- Shipping width: 100mm
- Shipping length: 450mm
- EAN: 4060537026849

NO IMAGE
AVAILABLE

Table of Contents

- [Startpage](#)
- [Safety Instruction Guide for 3-27x56 PM II High Power Riflescope](#)
- [About Us](#)

Safety Instruction Guide for 3-27x56 PM II High Power Riflescope

Introduction

Thank you for choosing the 3-27x56 PM II High Power Riflescope from Schmidt and Bender. This guide provides essential safety instructions and guidelines to ensure the safe use of your riflescope. Please read this document carefully before using the product.

General Safety Guidelines

- Ensure that the riflescope is used in accordance with local laws and regulations regarding firearms and optics.
- Always handle the riflescope with care to avoid damage.
- Store the riflescope in a secure location, out of reach of children and unauthorized users.
- Regularly inspect the riflescope for any signs of damage or wear.
- Do not use the riflescope if it is damaged or malfunctioning.
- Be aware of your surroundings and ensure that you have a clear line of sight before aiming and firing.
- Follow all safety protocols associated with firearms when using the riflescope.

Specific Safety Precautions for Use

- Always keep the riflescope pointed in a safe direction.
- Use appropriate eye protection when using firearms equipped with this riflescope.
- Ensure that the riflescope is properly mounted and securely fastened to the firearm before use.
- Adjust the magnification and focus settings only when the firearm is not in use.
- Avoid looking directly at bright light sources through the riflescope to prevent eye damage.
- Be cautious of recoil and ensure a firm grip on the firearm when shooting.
- Do not attempt to disassemble or modify the riflescope.

Instructions for Installation and Usage

1. Installation:

- Select a suitable mounting base for your firearm.
- Align the riflescope with the mounting base.
- Securely fasten the riflescope using the provided rings and screws.
- Ensure that the riflescope is level and properly positioned for optimal eye relief.

2. Usage:

- Before using the riflescope, adjust the eyepiece for optimal clarity.
- Set the desired magnification using the magnification ring.
- Adjust the windage and elevation turrets according to your shooting needs.
- To adjust parallax, turn the parallax adjustment knob to the appropriate setting based on the distance to your target.
- Always practice at a safe shooting range before using the riflescope in the field.

Disposal Instructions

- Dispose of the riflescope in accordance with local regulations regarding electronic waste and hazardous materials.
- Do not dispose of the riflescope in regular household waste.

- If the riflescope is damaged beyond repair, consider recycling components where possible.

Contact Information for Further Support

For any inquiries or concerns regarding the safety and use of the 3-27x56 PM II High Power Riflescope, please contact the appropriate local authorities or the manufacturer directly.

By following these safety instructions, you can ensure a safe and enjoyable experience with your 3-27x56 PM II High Power Riflescope. Thank you for your attention to safety.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk