

3-27x56 PM II High Power - 3-27x56 PM II High Power LP P4FL 1cm ccw DT35 MTC LT / ST ZC CT

[Optics & Mounting](#) > [Scopes](#) > [Rifle Scopes](#)

The 3-27x56 PM II High Power from Schmidt and Bender is a premier tactical riflescope engineered for ultimate versatility—capable of precise performance from near-range engagements all the way to extreme long-distance targets. With an expansive 3-27x magnification range, this scope adapts effortlessly across calibres and mission profiles.

Its 56 mm objective lens offers exceptional light gathering and clarity, enabling detailed target acquisition even at great distances. The field of view spans approximately 13.0-1.4 m at 100 m, while the exit pupil ranges around 8.7-2.1 mm. Generous eye relief of around 90 mm ensures comfortable alignment and a stable sight picture.

Built on a rugged 34 mm main tube, the scope is constructed for demanding environments. The turret system accommodates ultra-fine click values (e.g., ~0.1 mrad) and massive internal adjustment ranges for elevation and windage—making it suitable for long-range engagement scenarios. Parallax adjustment commonly spans from around 10 m to infinity, giving flexibility across varied target distances.

Key Specifications:

Magnification: 3-27x

Objective Lens Diameter: 56 mm

Main Tube Diameter: 34 mm

Field of View: approx. 13.0-1.4 m @100 m

Exit Pupil: approx. 8.7-2.1 mm

Eye Relief: approx. 90 mm

Click Value: approx. 0.1 mrad (~0.5 cm @100 m) depending on configuration

Parallax: from ~10 m to infinity

Crafted with German precision, the 3-27x56 PM II High Power is ideal for professionals, competition marksmen or hunters who demand the highest optical clarity, mechanical resilience and full versatility across a wide range of engagement distances.

Attributes

- Name: [3-27x56 PM II High Power LP P4FL 1cm ccw DT35 MTC LT / ST ZC CT](#)
- Manufacturer: [SCHMIDT U. BENDER](#)
- Product no.: EU2015950
- Mfr. No.: 669-911-972-F1-E8
- Colour: Black
- Delivery weight: 2kg
- Shipping height: 100mm
- Shipping width: 100mm
- Shipping length: 450mm
- EAN: 4060537064872

NO IMAGE
AVAILABLE

Table of Contents

- [Startpage](#)
- [Safety Instruction Guide for the 3-27x56 PM II High Power](#)
- [About Us](#)

Safety Instruction Guide for the 3-27x56 PM II High Power

Introduction

Thank you for choosing the 3-27x56 PM II High Power tactical riflescope by Schmidt and Bender. This guide provides essential safety instructions to ensure the safe and effective use of your product. It is designed to comply with the EU General Product Safety Regulation (GPSR) to protect your safety and wellbeing.

General Safety Guidelines

- Ensure that the riflescope is used only as intended and in accordance with the manufacturer's instructions.
- Always inspect the product for any visible damage before use.
- Keep the riflescope out of reach of children and unauthorized users.
- Use the product only in environments suitable for its design and construction.
- Report any unsafe conditions or accidents involving the product to the appropriate authorities.
- Stay informed about recall updates on the EU's Safety Gate platform.

Specific Safety Precautions for Use

- **Handling:** Always handle the riflescope with care to avoid dropping or damaging it.
- **Mounting:** Ensure the riflescope is properly mounted on the firearm to prevent accidents during use.
- **Eye Protection:** Always wear appropriate eye protection when using the riflescope to prevent injury from recoil or debris.
- **Environmental Considerations:** Avoid using the riflescope in extreme weather conditions that may impair its performance.
- **Maintenance:** Regularly clean the lenses and check all mechanical parts for proper functioning.
- **Storage:** Store the riflescope in a dry, secure location when not in use to prevent damage.

Instructions for Installation and Usage

1. Installation:

- Select a suitable firearm compatible with the 3-27x56 PM II High Power.
- Mount the riflescope securely onto the firearm using the appropriate mounting rings and bases.
- Ensure all screws are tightened according to the manufacturer's specifications to prevent loosening during use.

2. Adjustment:

- Adjust the magnification by rotating the magnification ring to the desired level.
- Use the turret system to make precise adjustments for elevation and windage as needed.

3. Focusing:

- Look through the riflescope and adjust the eyepiece to achieve a clear sight picture.
- Use the parallax adjustment to eliminate any parallax error based on your target distance.

4. Usage:

- Take a stable shooting position and align the riflescope with the target.
- Ensure a proper grip on the firearm and maintain a safe shooting stance.

- After taking your shot, observe the target through the riflescope for feedback.

Disposal Instructions

- Dispose of the product in accordance with local regulations regarding electronic and optical devices.
- Do not dispose of the riflescope in regular household waste.
- Consider recycling options available in your area to minimize environmental impact.

Contact Information for Further Support

For any questions or concerns regarding the use or safety of the 3-27x56 PM II High Power riflescope, please refer to the manufacturer's customer support resources. Ensure you have your product details ready for efficient assistance.

Thank you for your attention to these safety instructions. Enjoy your experience with the 3-27x56 PM II High Power riflescope while prioritizing safety and responsibility.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk