

# 5-45x56 PM II High Power - 5-45x56 PM II High Power LP TREMOR3 1cm cw DT27 MTC LT / ST ZC CT

[Optics & Mounting](#) > [Scopes](#) > [Rifle Scopes](#)

The 5-45×56 PM II High Power is a professional-grade precision optic that merges a high-performance rifle scope with spotting-scope capability. Designed for observation and ultra-long-range engagement, its enormous 9× zoom range (5-45×) makes it equally at home on reconnaissance, match, or tactical platforms where both identification and shot-making accuracy are required.

Engineered for extreme clarity and reach, the 56 mm objective delivers excellent light gathering while the optical system maintains a large usable field of view across the entire zoom range — allowing fast situational awareness at low magnification and razor-sharp detail at high power. The reticle sits in the first focal plane, so hold-offs and subtensions remain precise at any magnification. The model features robust, lockable turrets with fine 0.1 mrad click values and very large usable internal adjustment ranges tailored for extreme-range correction.

Built on a rugged 34 mm main tube, the High Power is constructed for demanding environments: it is fully weatherproof, fogproof and shock-resistant. Despite its long reach, the design balances mechanical strength with practical ergonomics for field use.

## Standout Features

- Exceptional 5-45× magnification range for combined observation and precision shooting
- Large 56 mm objective for outstanding light transmission and image resolution
- First focal plane reticle for accurate ranging and holdover at any magnification
- Precision turrets with 0.1 mrad click value and extensive elevation/windage adjustment range
- Side/parallax adjustment for crisp focus from mid-range to extreme distances
- High optical transmission (~90%) and illuminated reticle options for low-light operations
- Robust 34 mm tube, weatherproof and built for professional use

## Key Specifications

- Magnification: 5-45×
- Objective diameter: 56 mm
- Main tube diameter: 34 mm
- Field of view: approx. 7.8-0.9 m @ 100 m
- Exit pupil: approx. 8.8-1.2 mm
- Eye relief: 90 mm
- Length: approx. 434 mm
- Weight: approx. 1,130 g
- Reticle: FFP (various tactical reticle options)
- Click value: 0.1 mrad
- Elevation adjustment range: ~27 mrad (internal ~29.6 mrad)
- Windage adjustment range: ±6 mrad (internal ~21.1 mrad)

NO IMAGE  
AVAILABLE

Parallax: adjustable

Illumination levels: multiple (illuminated reticle available)

Optical transmission: ~90%

Designed and manufactured to professional standards, the 5-45×56 PM II High Power is the go-to optic for operators and precision shooters who require unmatched versatility, extreme reach and uncompromising optical and mechanical performance.

## Attributes

- Name: [5-45x56 PM II High Power LP TREMOR3 1cm cw DT27 MTC LT / ST ZC CT](#)
- Manufacturer: [SCHMIDT U. BENDER](#)
- Product no.: EU2015980
- Mfr. No.: 666-911-532-G9-E9
- Colour: Black
- Delivery weight: 2kg
- Shipping height: 100mm
- Shipping width: 100mm
- Shipping length: 450mm
- EAN: 4060537014723

# Table of Contents

- [Startpage](#)
- [Safety Instruction Guide for 5-45x56 PM II High Power](#)
- [About Us](#)

# Safety Instruction Guide for 5-45x56 PM II High Power

## Introduction

Thank you for purchasing the 5-45x56 PM II High Power. This precision optic is designed for professional use, combining highperformance features for observation and shooting at extended ranges. To ensure your safety and the optimal performance of this product, please read this safety instruction guide carefully.

## General Safety Guidelines

- **Product Safety:** This product is designed to meet safety standards for nonfood items. Always use it as intended to avoid hazards.
- **Enhanced Recalls:** Be aware that any recalls will be communicated through standardized notices. If a safety issue arises, free remedies will be provided.
- **Online Shopping:** If purchased online, this product has the same safety protections as those bought in physical stores.
- **Special Consumer Focus:** Extra precautions are in place to protect vulnerable groups, including children. Keep this product out of reach of children.
- **EU Contact Point:** For any safety inquiries regarding this product, there will be an EUbased contact available.
- **Rapid Alerts:** Stay informed about any unsafe products through the EU's Safety Gate platform.

## Specific Safety Precautions for Use

- **Avoid Eye Injury:** Never look directly at the sun or any intense light source through the optic, as this can cause severe eye damage.
- **Secure Mounting:** Ensure that the optic is securely mounted to prevent it from loosening during use, which could lead to loss of control or accuracy.
- **Proper Handling:** Handle the optic with care to avoid dropping or impacting it, which may compromise its integrity.
- **Environmental Considerations:** Avoid exposing the optic to extreme temperatures or moisture beyond its specified limits.
- **Cleaning:** Use only approved cleaning materials and methods to avoid damaging the optical surfaces.

## Instructions for Installation and Usage

### 1. Installation:

- Ensure your rifle is unloaded before installation.
- Use appropriate mounting rings compatible with the 34 mm main tube.
- Securely attach the optic to the rifle, ensuring it is aligned with the barrel for accurate shooting.

### 2. Usage:

- Adjust the magnification as needed using the zoom control.
- Use the side/parallax adjustment to focus the image based on your distance from the target.
- Always check the reticle alignment and make necessary adjustments using the precision turrets.
- Keep the optic covered when not in use to protect it from dust and debris.

## Disposal Instructions

- **General Disposal:** Dispose of the product in accordance with local regulations regarding electronic waste and optics.
- **Environmental Responsibility:** Ensure that any batteries or electronic components are recycled according to local guidelines to minimize environmental impact.

## Contact Information for Further Support

For any questions or concerns regarding the 5-45x56 PM II High Power, please refer to the manufacturer's contact information provided on the product packaging or manual.

By following these safety instructions, you can ensure a safe and effective experience with your 5-45x56 PM II High Power optic. Thank you for your attention to these guidelines, and enjoy your product!

# About Us

## Brownells UK

### **Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories**

Unit 1, Laughing Dog Industrial Estate  
London Road  
Rugby  
Warwickshire  
CV23 9LP

[www.brownells.co.uk](http://www.brownells.co.uk)